

變壓器測試

規格比較表

型號	5265	5266	5267	5465	5466	5467
產品						
測試頻率(Hz)	10-200k	10-500K	10-1M	10-200k	10-500k	10-1M
測試通道數	20			48		
測量頻率解析度	五位數			五位數		
AC測試信號電壓	10mV-2Vrms			10mV-2Vrms		
圈數比頻率(Hz)	50-200k			50-200k		
輸出阻抗	100Ω			100Ω		
LCR Meter 功能	●	●	●	●	●	●
L, LK	0.1nH-9999.99H			0.1nH-9999.99H		
C	0.00001pF-999.99mF			0.00001pF-999.99mF		
Q,D	0.00001-99999			0.00001-99999		
Z,X,R	0.00001Ω-99.9999MΩ			0.00001Ω-99.9999MΩ		
Y	0.01nS-99.9999S			0.01nS-99.9999S		
θ	-180°-+180°			-180°-+180°		
DCR	0.1mΩ-99.999 MΩ			0.1mΩ-99.999 MΩ		
Turn-Ratio	0.1-99999.9 turns			0.1-99999.9 turns		
Pin-Short	12 pairs, between pin to pin			24 pairs, between pin to pin		
測試治具	F5620			F5648		
測試治具含直流偏置電流	100mA			100mA		
內建儲存測試檔案	128組			128組		
電腦連線軟體	●			●		
介面	RS-232、Handler、LAN、USB Host、EXT. I/O			RS-232、Handler、LAN、USB Host、EXT. I/O		
液晶螢幕顯示	800*480 7吋彩色			800*480 7吋彩色		

備註：● 代表有此功能；— 代表無此功能